

Easy Access/Walk-In Bath

USER GUIDE



PLEASE READ THE FOLLOWING CAREFULLY AND RETAIN.
IMPROPER USE OR CARE CAN INVALIDATE THE WARRANTY.

The Easy Access bath features a watertight door held firmly in a locked position by means of cam lock catches operated by a lever activated steel handle. The door should always be kept in an open position when not in use to prevent wear out of the door seal.

- 1) When seated in the bath plug up the wastes and push the door to close.
- 2) Push the steel handle away from you fully until it reaches the stop position. The bath is now watertight and ready for use.
- 3) Turn the taps on and fill the bath to desired depth.
- 4) After bathing release the two wastes and if necessary remain seated until all the water is completely drained away.
- 5) Pull on the door handle towards you to unlock the door.
- 6) Exit the bath and leave the door unlocked when not in use to preserve the door seal.

CARE AND MAINTENANCE

The bath is manufactured to a very high standard to ensure its durability and appearance over many years of use. It has a robust, smooth and warm surface that is non-porous, resistant to dirt and bacteria and easy to clean and maintain.

This bath will give many years of service and continue to look good if cleaned correctly and treated with care.



Trojan Plastics Ltd.
Ramsden Mills, Britannia Road, Huddersfield,
West Yorkshire HD3 4QG

CAUTION

- ALWAYS LEAVE THE DOOR OPEN WHEN THE BATH IS NOT IN USE TO PRESERVE THE DOOR SEAL.
- KEEP THE WHITE SILICONE SEAL FREE OF ANY BUILD-UP OF DEPOSITS. CLEAN GENTLY AND AVOID UNNECESSARY HANDLING.
- DO NOT LEAN ON DOOR OR USE FOR SUPPORT.
- NEVER ATTEMPT TO OPEN THE DOOR WHEN THE BATH IS FULL OF WATER.

CLEANING

- 1) As with standard baths, cleaning will vary subject to the scale residue dependant on the hard or soft water level. In soft water areas, wash down with warm water and detergent applied with a soft cloth or sponge. In hard water areas, non-abrasive or mild acid cleansers can be used. Clean regularly followed by wiping with a dry soft cloth.
- 2) The stainless steel door lever handle should be polished occasionally to prevent discolouring. Use a metal polish or multi-surface polish/cleaner.
- 3) The white silicon seal along the bath door sides should be cleaned occasionally. Use detergent and warm water applied with a sponge or soft cloth. Apply gently and refrain from excessive rubbing.
- 4) Ideally all chrome or gold plated furniture should be wiped down dry after use.
- 5) Clean with soapy water and buff with a dry soft cloth only. Note: Surfaces can be damaged with acid/abrasive cleaners or with a rough cloth/sponge.